



ARS

www.buchananrubber.com

FLEXLITE



FLEXLITE

ARS

- Provides 3 times the wear resistance of resin hoses
- SBR blended tube provides exceptional wear resistance
- Flexible to -40F
- Used in a variety of material handling application where a superior resistance to abrasion is required, such as transfer of crushed rock, sand, pea gravel, cement, dry fertilizer, grain and ore.
- Cover and tube are specially formulated static dissipative compound



Item #	Ø Ins.	Ø Out	Weight	WP	Vacuum	Bending radius	Roll Length
	[inch]	[inch]	[lb/ft]	[psi]	[HG]	[inch]	[ft]
ARS-150	1-1/2	1.82	.37	45	29	2.00	100
ARS-200	2	2.35	.50	40	29	2.50	100
ARS-250	2-1/2	2.95	.73	35	29	2.50	100
ARS-300	3	3.50	1.10	35	29	3.00	100
ARS-400	4	4.63	1.77	30	29	4.50	100
ARS-500	5	5.76	2.47	30	28	5.00	100
ARS-600	6	5.76	3.08	30	28	9.20	100
ARS-800	8	9.04	5.65	30	27	15.00	60

www.buchananrubber.com

TORONTO - MONTREAL - EDMONTON - HOUSTON

50 Fasken
Dr,
Toronto, ON
M9W1K5

9555 Henri
Bourassa W,
St Laurent, QC
H4S1S7

9547-12Ave
SW,
Edmonton, AB
T6X0C3

5731 Harvey
Wilson Dr,
Houston, TX
77020